

Price List and Specs.

Item	Description	Unit Price
1201	1' x 1' x 1/2" Tongue & Groove Tile 64 sf. 64 tiles/box	\$44.80
1202	1' x 1' x 1/2" Tongue & Groove Tile 64 sf. 64 tiles/box	\$44.80
1205	1' x 1' x 1/2" Tongue & Groove Tile 64 sf. 64 tiles/box	\$44.80
1207	1' x 1' x 1/2" Tongue & Groove Tile 64 sf. 64 tiles/box	\$44.80
1225	1' x 1' x 1/2" Tongue & Groove Tile 64 sf. 64 tiles/box	\$44.80
2458F	2' x 2' x 5/8" Standard Tile 192 sf. 48 tiles/box	\$134.40
2424F	2' x 2' x 1" Standard Tile 120 sf. 30 tiles/box	\$96.00
2424T-02/07	2' x 2' x 1" Tegular Edge Tile 120 sf. 30 tiles/box	\$103.20
1220	2' X 2' X 1" Clean Room Tile 120 sf. 30 tiles/box	\$118.80
2201	2' x 2' x 1" Pyramid Tile 112 sf. 28 tiles/box	\$109.60
5827F	2' x 4' x 5/8" Standard Tile 192 sf. 24 tiles/box	\$134.40
4124F	2' x 4' x 1" Standard Tile 120 sf. 15 tiles/box	\$96.00
4224T-02/07	2' x 4' x 1" Tegular Edge Tile 120 sf. 15 tiles/box	\$100.80
1240	2' x 4' x 1" Clean Room Tile 120 sf. 15 tiles/box	\$118.80

MOLDED POLYSTYRENE CEILING TILE SPECS.

Tile Thickness	1/2"	5/8"	1"
Density*	1.5	1.5	1.5
Flame Spread*	5	5	5
Smoke Density*	15-50	15-50	15-50
Thermal conductivity R value*	2	2.5	4.55
Coeff. Of thermal expansion	0.00004		
Effective temperature intermittent	Max. 180F		
Compressive strength at 5% deflection (a)	23		
Flexural strength	63		
Capillarity	None		
Water vapor transmission	0.7 - 1.3		
Water absorption (by volume)	Less then 1.5		
Fuel contribution	0		
Smoke toxicity	Less then wood		
Light reflectance	Grade LR 1 Reflects 94% of light		

All ceiling tiles are class "A" fire rated and can be installed below fire sprinklers as melt away tile

THERMO-TILE specifications starred(*) are Flame Spread and Smoke Development Recorded while the material remains in the original test position.